

**People Movers** 

48-4L



## Let's get moving.


With families and guests in mind, our Star EV People Movers can shuttle large groups safely and comfortably. Standard features include high-back seats, rack-and-pinion steering and smooth leaf spring suspensions. We have shuttles that can seat 4 to 8 passengers and buses to accommodate 8 to 28 passengers. Now that's moving people!

- Eight 6V (48V) batteries required
- 4 Passengers all facing forward
- 5.5HP DC Motor (48V)
- 400 amp (48V) Curtis programmable controller with regenerative braking
- Rear view mirrors on both sides
- Retractable seat belts
- Functional front and rear bumpers
- Curtis battery indicator
- Horn, reverse beep, parking brake
- Head lights, taillights, brake lights, turn signals
- 48V to 12V voltage reducer for all accessories
- Foldable tinted windshield
- 10-inch Aluminum wheels
- Plastic battery box
- High/Low speed selection switch
- Easy access program/troubleshooting port under dash

- Aluminum or stainless steel side rails
- Tan seats
- Extended color matching canopy with grab handles
- Automatic battery charger included
- 19.5mph (17MPH Low Speed Rear, 20-25mph if LSV)
- 123"Lx47"Wx77"H
- Four-year limited warranty

## **OPTIONS**

- LSV (NEV) Street Legal Package
- 10:1 High Speed rear end
- Wood grain dash, steering wheel, seat back cover
- AC System Upgrade
- 12" aluminum wheels (shown)
- Single piece DOT AS1 glass windshield with or without wiper



## Specifications for 4 Passenger Long\*

Specs Star-48-4L

Passenger

Battery System, V

Motor Power, HP

Controller Power, A

Top Speed, MPH

Load Capacity, lbs

4, all facing forward

8x6V, Trojan T105 recommended

5.5 HP Continuous ADC Motor

400A Curtis 1268

19.5mph (17MPH Low Speed Rear,20-25mph if LSV)

Dimension, inch

123"Lx47"Wx77"H

Weight, lbs

850lbs without batteries

Ground Clearance, inch
Turning Radius, ft.

Wheel Base
Top Climbing Grade
Body Material

5"
12 ft
96"
20%
Plastic

Front Suspension

Rear Suspension

Steering System

Brake System

Leaf spring & shock
Leaf spring & shock
Rack and pinion
Rear drum

Tire Size 205x50-10 4PLY, DOT

Tire Pressure, PSI 30 PSI

Wheel Type 10 inch Polished Aluminum

Chassis

Roof Fiberglass, color matched & extended Drive Train Direct rear drive with 12.49:1 ratio

Voltage Reducer 20A, 48V to 12V included

Windshield Foldable tinted
Head Lights Included
Tail Lights Included
Brake Lights Included
Turning Signals Included
Horn Included

Reverse Beeper Included

Seat Belts 2 point seat belt included for each person

Side View Mirrors Included
Battery Indicator Included


Battery Box Included for center 6 batteries

High/Low Speed Switch Included
Golf Bag Holder Included
Automatic Battery Charger Included

Warranty

Proudly Presented By

Limited 4-Year parts and labor





High back seating



High/Low Speed Switch



Optional 12" machined wheel aluminum



Rack and pinion steering; solid front bumper