

**People Movers** 48-6L

## Let's get moving.

With families and guests in mind, our Star EV People Movers can shuttle large groups safely and comfortably. Standard features include high-back seats, rack-and-pinion steering and smooth leaf spring suspensions. We have shuttles that can seat 4 to 8 passengers and buses to accommodate 8 to 28 passengers. Now that's moving people!




- Eight 6V (48V) required
- 6 Passengers, all facing forward
- 5.5HP ADC Motor
- 400 amp (48V) Curtis programmable controller with regenerative braking
- 4 Wheel Hydraulic Drum Brakes
- Rear view mirrors on both sides
- Retractable seat belts for each passenger
- Functional front and rear bumpers
- Curtis battery indicator
- Horn, reverse beep, parking brake
- Head lights, taillights, brake lights, turn signals
- 48V to 12V voltage reducer for all accessories
- Foldable tinted windshield
- 10-inch Aluminum wheels
- Plastic battery box

- Stainless steel side rails
- Tan seats
- Extended color matching canopy with grab handles
- Automatic battery charger included
- 19.5 MPH (17mph-Low Speed Rear, 20-25mph with LSV option)
- 153"Lx47"Wx77"H
- Four-year limited warranty

## **OPTIONS**

- LSV (NEV) Street Legal Package
- 10:1 High Speed rear end
- Wood grain dash, steering wheel, seat back cover
- AC System Upgrade
- Single piece DOT (AS1) windshield with or without wiper
- 2-in-1 combo or rear flip seat
- High/Low speed selection switch




\*Extra charge for yellow

Star EV (Division of) JH GLOBAL SERVICES, INC 378 Neely Ferry Rd. Simpsonville, SC 29680, USA phone:864.297.8833 fax: 864.297.7010 toll free: 1.877.818.8833 www.starev.com

## Specifications for 6 Passenger Long People Movers\*

Star-48-6L Specs 6, all facing forward Passenger 8x6V, Trojan T105 recommended Battery System, V 5.5 HP Continuous ADC Heavy Duty Motor Power, HP 400A Curtis 1244 Controller Power, A 19 MPH (17 if Low Speed Rear, 20-25 if LSV) Top Speed, MPH 990 lbs Load Capacity, lbs 153"Lx47"Wx77"H Dimension, inch 1200lbs without batteries Weight, lbs 5" Ground Clearance, inch 15 ft Turning Radius, ft. 125" Wheel Base 20% Top Climbing Grade Plastic **Body Material** Leaf spring and shock Front Suspension Leaf spring and shock Rear Suspension Rack and Pinion Steering System 4 Wheel hydraulic **Brake System** 205x50-10 4PLY, DOT Tire Size 30 PSI Tire Pressure 10 inch Aluminum Wheel Type Optional Rear Seat Fiberglass, color matched and extended Rood Direct rear drive with 12.49:1 ratio **Drive Train** 20A, 48V to 12V included Voltage Reducer Foldable tinted Windshield Included **Head Lights** Included Tail Lights Included Brake Lights Included **Turning Signals** Included Horn Included Reverse Beeper Included Seat Belts Included Rear View Mirrors Included **Battery Indicator** Included for center 6 batteries **Battery Box** Optional High/Low Speed Switch Included Automatic Battery Charger Limited 4-Year parts and labor Warranty

## Proudly Presented By





Extended roof protects all passengers from the elements



Rack and pinion steering; solid front bumper



Cup holders and dual storage compartment



Stylish 10" aluminum rims are standard